




LOW MAINTENANCE HIGH EFFICIENCY REDUCED LIFE-CYCLE COST



Long Life Filter

A proprietary combination of materials offers higher filtration efficiency with lower pressure drop, ensuring a safe journey for passengers.



Data sheet for information purpose only - all rights reserved.

Features

Knorr-Bremse has set a new benchmark in panel filters technology. Lasting up to 4 times longer than standard commercial panel filters, while occupying the same space, the long-life filter can be fitted in almost any new / old HVAC equipment¹.

Merak Long Life Filter




Standard Panel Filter



¹Relative filter service life depends on the environment and project application.

*The Merak Long Life Filter design is completely free of metal or glass-fiber parts. All componentes are based on pure-grade recyclable fibers.

Efficiency



Technical Data

Efficiency Class	ePM10 50%, according to ISO 16890 MERV 9 (ASHRAE 52.2)
Efficiency for 2.5 μm particles	After the first weeks of use: >80%
Dimensions fully customizable ²	W x H x D mm
Typical air speed range	1 – 2,5 m/s
Typical pressure drop	40 – 65 Pa
Max. operating moisture	100%
Fire & Smoke classification	HL3 (EN 45545-2 R5)

²Standard Depth: 48 mm.

We reserve the right to make technical modifications.

Knorr-Bremse España, S.A. Merak

Calle Miguel Faraday 1 28906 Getafe Spain Tel: +34 911 459 400 Fax: +34 911 459 444 merak@merak-hvac.com www.merak-hvac.com



Please, scan the code for more information about our locations



« (())»	KNORR-BREMSE
(K)»	NEW YORK AIR BRAKE
(((())))	IFE
« (())»	MERAK
«(K)»	MICROELETTRICA
«®»	SELECTRON
(K)»	EVAC
«®»	ZELISKO
((K))»	RAILSERVICES